

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/088427 A1

- (51) International Patent Classification⁷: H01R 13/72, 25/00
- (21) International Application Number: PCT/SG03/00090
- (22) International Filing Date: 17 April 2003 (17.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PI 20021435 18 April 2002 (18.04.2002) MY
- (71) Applicant (for US only): POWER BRIDGE (SINGAPORE) PTE. LTD [SG/SG]; Block 209 Bukit Batok St. 21, #13-172 Singapore 650209 (SG).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian

[Continued on next page]

(54) Title: EXTENSION SOCKET DEVICE WITH A CORD STORAGE AND DISPENSING SYSTEM



(57) Abstract: There is disclosed an extension socket device, electrically equipped with a plurality of socket units (15) and a cord storage and dispensing system. The present invention comprises a rectangular housing body (10) formed by two hollow parts, an electrical plug (22) and an extension cord (21). The larger hollow part of the housing body (10) comprises a top wall (11), two end walls (12) and two side walls (13). The smaller hollow part comprises a ring-like intermediate wall (17) and a bottom wall (14), wherein in the intermediate wall and a bottom wall, wherein the intermediate wall and the bottom wall integrally form a working enclosure defining a working space for the wiring mechanism of the socket units (15). A receiving track of predetermined space is formed when the larger hollow part and the smaller hollow part are assembled together. The extension cord (21) of predetermined length in single file is fully retracted into the receiving track. A plurality of flexible retainer means is integrally provided along the bottom edge of the smaller hollow part. Each retainer means covers partially the opening of the receiving track. The cord storage and dispensing system comprises the receiving track and the flexible retainer means.



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

EXTENSION SOCKET DEVICE WITH A CORD STORAGE AND DISPENSING SYSTEM

TECHNICAL FIELD

This invention relates generally to extension socket devices, and particularly to an
5 extension socket device with a cord storage and dispensing system.

BACKGROUND ART

Extension socket can provide multiple socket units for more than one electrical
appliance to share the power source from a common wall socket or any extension
socket. Prior art extension socket device comprises a housing body with multiple
10 socket units, an electrical plug, and an elongated extension cord connecting the plug
and the housing body. The length of the extension cord is often left exposed and can
be entangling.

United States Patent No. 6,142,405 discloses an extension cord storage and dispensing
system for conveniently storing and dispensing an elongated extension cord of various
15 lengths without entanglement and without requiring the unwrapping of the entire
length of extension cord to effectively utilise both ends. The inventive device
includes a second spool, a first spool and a handle. The two spools have preferably a
flat profile for convenient storage. The first spool receives a longer length of the
extension cord while the second spool receives a shorter length of the cord that is
20 commonly needed thereby separating the shorter length constantly dispensed and
stored from the longer length. The main disadvantage of this invention is that it is a
stand-alone device which is not directly connected to any electrical device. In actual
application, it becomes an additional carrying item.

United States Patent No. 6,077,109 discloses an extension socket, including a socket
25 body which consists of more than one socket units electrically connected each other,
an electrical plug, an extension wire having a predetermined length connecting
between the socket units and the electrical plug, and a receiver arrangement for
receiving the extension wire. The socket body includes a socket housing to install the
socket units therein. The socket housing has a top wall, a bottom wall and a

surrounding side wall between the top wall and the bottom wall, wherein the extension wire is extended from a wire outlet of the surrounding side wall to the electrical plug. The receiver arrangement is composed of a ring shaped protecting wall which is arranged to surround the socket housing of the socket body and has a
5 predetermined height, and a connecting wall extended from a top end of the protecting wall to the socket housing, wherein a receiving chamber is defined between the protective wall and the surrounding side wall of the socket housing. Thereby, the extension wire can be wound around the surrounding side wall of the socket housing within the receiving chamber. The main disadvantage of this invention is that a
10 separate receiver arrangement surrounding the socket body is required. The holding arm is also not efficient.

SUMMARY OF THE INVENTION

The present invention has therefore as an object to equip an extension socket device integrally with a cord storage and dispensing system, without increasing its
15 construction cost.

A further object of the invention is to provide a plurality of flexible retainer means along a smaller hollow part of a housing body. Each retainer means partially covers the opening of a receiving track, such that the movement of an extension cord is restrained.

20 These objects are achieved in that the housing body of the above extension socket device is provided integrally with the receiving track with sufficient space to accommodate the extension cord in single file.

BRIEF DESCRIPTION

In order that the present invention may be more readily understood, the following
25 description is given, by way of example, of one specific embodiment of an extension socket device made in accordance with this invention. Reference is made to the accompanying drawings, in which: -

Figure 1 is a perspective view showing the front of an extension socket device with an extension cord extended for use.

Figure 2a is a plan back view of this invention, without the extension cord.

Figure 2b shows in perspective the retracted position of the extension cord in single file, withdrawn from its actual position inside a receiving track of a housing body.

Figure 3a shows diagrammatically the relative position of the extension cord in single file when retracted inside the receiving track of the housing body.

Figure 3b shows an exploded perspective view of a flexible retainer means.

DETAILED DESCRIPTION

Like the prior art extension socket device, a substantially rectangular housing body (10) of this invention essentially is formed by two hollow parts (10a, 10b). The larger hollow part (10a) comprises a top wall (11), two end walls (12) and two side walls (13). The smaller hollow part (10b) comprises a ring-like intermediate wall (17) and a bottom wall (14). For ease of explanation, the larger hollow part (10a) is placed over the smaller hollow part (10b). The terms "top" and "bottom" are used according to this orientation. However, other orientations of the housing body (10) are possible.

A gang of three socket units (15) are provided on the top wall (11) of the rectangular housing body (10), as seen in Figure 1. Each socket unit (15) is operable from a switch (16). An extension cord (21) with an electrical plug (22) is fully extended from an outlet port (18) on one end wall (12) of the housing body (10).

At the back of the rectangular housing body (10) as seen in Figure 2a, the smaller hollow part (10b) of the housing body (10) defines a working enclosure, with a working space for the wiring mechanism of the socket units (15). An exit port (not seen) is also provided on the intermediate wall (17), for one end of the extension cord (21) to electrically connect to the wiring mechanism inside. A receiving track (19) is thus formed between the larger hollow part (10a) and the smaller hollow part (10b) of the housing body (10) when they are assembled together. The receiving track (19) takes the form of an open ring-like trough. At predetermined positions along the bottom edge of the smaller hollow part (10b), there is provided a plurality of flexible retainer means (20). Each retainer means (20) partially covers the opening of the

receiving track (19). The retainer means (20) serves to restrain the movement of the extension cord (21) in single file when it is retracted inside the receiving track (19).

Referring to Figure 2b, one end of the extension cord (21), in single file when it is fully retracted inside the receiving track (19), connects electrically to the wiring mechanism inside the working enclosure, through the exit port provided on the intermediate wall (17) of the smaller hollow part (10b). The width of the receiving track (19) is designed in such a way that there is sufficient space for a single file of the extension cord (21). This helps to restrain the movement of the extension cord (21). The extension cord (21) is wound round the perimeter of the working enclosure several times. Depending on the predetermined depth of the receiving track (19) according to the design of the invention, predetermined rounds or complete turns of the extension cord (21) are allowed. In Figure 2b, four turns are shown. The other end of the extension cord (21) is disposed outermost to the housing body (10). An outlet port (18) is integrally provided at one end wall (12) of the larger hollow part (10a), to allow this other end of the extension cord (21) to exit from the housing body (10), and connectable to an electrical plug (22).

As clearly seen in Figure 3a, the receiving track (19) is defined by the larger and smaller hollow parts (10a, 10b) of the housing body (10). Four turns of the extension cord (21) are retracted into the receiving track (19), one on top of the other in single file. A plurality of flexible retainer means (20) takes the form of an inverted L-shaped element integrally provided along the bottom edge of the smaller hollow part (10b). The horizontal arm of the L-shaped element covers partially the opening of the receiving track (19). As seen in Figure 3b, space is also provided between the inverted L-shaped element and the intermediate wall (17), wherein a slight flexibility is allowed. In other words, the flexible retainer means (20) are integrally moulded as structural features of the smaller hollow part (10b) of the housing body (10). The receiving track (19) and the flexible retainer means (20) therefore constitute a cord storage and dispensing system for the present invention.

CLAIMS

- 1) An extension socket device, electrically equipped with a plurality of socket units (15) and a cord storage and dispensing system, comprises a rectangular housing body (10) formed by two hollow parts (10a, 10b), an electrical plug (22) and an extension cord (21) wherein
- 5 the larger hollow part (10a) of the rectangular housing body (10) comprises a top wall (11), two end walls (12) and two side walls (13);
- the smaller hollow part (10b) comprises a ring-like intermediate wall (17) and a bottom wall (14), wherein the smaller hollow part (10b) contains a working enclosure defining a working space for the wiring mechanism of the socket units (15),
- 10 is characterised in which
- a receiving track (19) of predetermined space is formed between the larger hollow part (10a) and the smaller hollow part (10b) when assembled; and
- 15 a plurality of flexible retainer means (20) is integrally provided along the bottom edge of the smaller hollow part (10b);
- whereby the extension cord (21) of predetermined length in single file can be fully retracted into the receiving track (19).
- 2) An extension socket device with a cord storage and dispensing system as in Claim 1 wherein the predetermined length of the extension cord (21) depends on the
- 20 number of turns around the perimeter of the working enclosure.
- 3) An extension socket device with a cord storage and dispensing system as in Claim 1 wherein the flexible retainer means (20) takes the form of an inverted L-shaped element integrally provided along the bottom edge of the smaller hollow part (10b), wherein the horizontal arm of the L-shaped element covers partially the
- 25 opening of the receiving track (19), and space is also provided between the inverted L-shaped element and the intermediate wall (17).
- 4) An extension socket device with a cord storage and dispensing system as in Claim 1 wherein the cord storage and dispensing system comprises the receiving track
- 30 (19) and the flexible retainer means (20).

- 5) An extension socket device with a cord storage and dispensing system as in Claim 1 wherein the flexible retainer means (20) are integrally moulded as structural features of the smaller hollow part (10b) of the housing body (10).

1/5




Figure 1




Figure 2a

3/5




Figure 2b




Figure 3a




Figure 3b

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SG 03/00090-0

CLASSIFICATION OF SUBJECT MATTER

IPC⁷: H01R 13/72, 25/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: H01R 13/502, 13/72, 25/00; H02G 11/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5071367 A (LUU D. H. V.) 10 December 1991 (10.12.91) <i>the whole document.</i>	1-5
A,P	EP 1233481 A1 (SDG IND LTD.) 21 August 2002 (21.08.02) <i>the whole document.</i>	1-5
A	WO 02/33791 A1 (POWER BRIDGE S.) 25 April 2002 (25.04.02) <i>abstract and fig. 2b.</i>	1-5

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

„A“ document defining the general state of the art which is not considered to be of particular relevance

„E“ earlier application or patent but published on or after the international filing date

„L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other means

„P“ document published prior to the international filing date but later than the priority date claimed

„T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

„&“ document member of the same patent family

Date of the actual completion of the international search

4 July 2003 (04.07.2003)

Date of mailing of the international search report

12 August 2003 (12.08.2003)

Name and mailing address of the ISA/AT

Austrian Patent Office
Dresdner Straße 87, A-1200 Vienna
Facsimile No. 1/53424/535

Authorized officer

KOSKARTI F.

Telephone No. 1/53424/326

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SG 03/00090-0

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
EP	A1	1233481	21-08-2002	FR	A1	2820889	16-08-2002
US	A	5071367	10-12-1991	CA	AA	2005841	06-04-1991
				CA	C	2005841	02-04-1996
				EP	A1	421906	10-04-1991
				JP	A2	3201377	03-09-1991
WO	A	233791		none			